

ZPXK2.E365037 - Wiring, Printed - Flexible Material Constructions - Component

Wiring, Printed - Flexible Material Constructions - Component


See General Information for Wiring, Printed - Flexible Material Constructions - Component

RELIANCE TECHNOLOGY DEVELOPMENT LTD

E365037

UNIT H, 14TH FLOOR
MAI LUEN INDUSTRIAL BUILDING
23-31 KUNG YIP STREET
KWAI CHUNG, N T, HONG KONG

Type	Cond Width		Cond Thk mic(mil)	SS/ DS/ DSO	Max	Max		Meets UL796F DSR	C T		
	Min mm(in)	Min Edge mm(in)			Area Diam mm(in)	Solder Limits C sec	Oper Temp C			Flame Class	
Flexi-to-Install, Single layer flexible materials interconnect constructions.											
RT-F1	0.06 (0.002)	0.10 (0.004)	12 (0.47)	DS	50.8 (2.0)	288	10	105	V-0	-	4
Rigid, Single layer flexible materials interconnect constructions.											
RT-F2	0.06 (0.002)	0.10 (0.004)	12 (0.47)	DS	50.8 (2.0)	280	10	105	V-0	All	0

Marking: Company name or trademark  or file number and type designation. May be followed by a suffix to denote factory identification or burning test classification.

Last Updated on 2019-05-30

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"